COALA ROLL-UP PP S

MATERIAL DESCRIPTION

Coala Roll-up PP S is a 195 mic white matt polypropylene with grey back. Coala Roll-up PP S is opaque with block out properties, and anti-curl. It is the perfect choice for promotional roll-up.

PRINTER & INK COMPATIBILITY

ECO solvent **solvent** **LATEX inkjet** **UV inkjet**

FILM THICKNESS

195 µ

GRAMMAGE

160 g/m²

PRODUCT DESCRIPTION

- Thickness: 195 mic
- Grammage: 160 g/m²
- Gloss 60°: 15.0 % (ASTM D2457)
- Gloss 85°: 30.0 % (ASTM D2457)
- Shade(fs): L*: 90
           a* 0
           b* -5
  (ANSI T) (D50/2°/Abs/No)

APPLICATIONS

- Roll-up
- Posters
- Points of sales
- Trade show graphics

PRINTING AND LAMINATING

- Suitable printing condition:
  Temperature 15~30°C(59~86°F) / Humidity 30~60%
- Use care in handling printed material, surface susceptible to abrasion
- To optimize the printing quality, printer need to be set for highest print quality.
- Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, prints have to be completely dry before undergoing further processing or lamination.

BENEFITS

- High image quality along with durability, tear-resistance, and anti-curl properties.
- Good scratch and water resistance
- Very good flatness
- Eco-friendly PVC free product

PVC FREE

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

SHELF LIFE STORAGE AND CONDITIONS

- It is recommended to store in the closed original packing in a cool and dry environment
- Temperature: 10°~25°C, Relative Humidity 50% RH
- Processing: within one year after receipt

antalis™
Just ask Antalis